


BIOPHARMACEUTICALS



Separation of Amino Acids by HILIC/ Single Quadrupole Mass Detection





Representative spectra of 21 standard amino acids separated on a HALO® Glycan column are shown. Amino acid isomers (e.g., Leu, Ile), as well as amino acids: Gln and Lys, are detected under the same mass channels (m/z 132.1 and 147.1, respectively). The elution order for the isomers is Leu first, followed by Ile. The target amino acid is specified with an asterisk (*) symbol in chromatograms showing multiple peaks (e.g., Cys, Thr, Asn, Glu, Asp).

PEAK IDENTITIES:

Amino Acid	Acronym	Monoisotopic mass ^{ref 2} [M]	SIR mass ^{ref 6} [M+H ⁺]
Alanine	Ala, A	89.1	90
Arginine	Arg, R	174.2	175
Asparagine	Asn, N	132.1	133
Aspartic acid	Asp, D	133.1	134
Cysteine	Cys, C	121.2	122
Cystine ^{ref 7}	n/a	240.3 ref 7	241
Glutamic acid	Glu, E	147.1	148
Glutamine	Gln, Q	146.2	147
Glycine	Gly, G	75.1	76
Histidine	His, H	155.2	156
Isoleucine	lle, I	131.2	132
Leucine	Leu, L	131.2	132
Lysine	Lys, K	146.2	147
Methionine	Met, M	149.2	150
Phenylalanine	Phe, F	165.2	166
Proline	Pro, P	115.1	116
Serine	Ser, S	105.1	106
Threonine	Thr, T	119.1	120
Tryptophan	Trp, W	204.2	205
Tyrosine	Tyr, Y	181.2	182
Valine	Val, V	117.1	118







BIOPHARMACEUTICALS



Separation of Amino Acids by HILIC/ Single Quadrupole Mass Detection

TEST CONDITIONS:

Column: HALO 90 Å Glycan, 2.7 µm, 2.1 x 100 mm

Part Number: 92922-605

Mobile Phase A: 85/15 Acetonitrile/ 10 mM ammonium formate, 0.15% Formic Acid

Mobile Phase B: 10 mM ammonium formate pH 3.0, 0.15% Formic Acid

 Gradient:
 Time 0.0
 %B 0.0

 10.0
 5.0

 15.0
 37.5

 15.5
 95.0

 20.0
 95.0

 20.5
 0.0

 25.0
 0.0

Flow Rate: 0.4 mL/min

Column Temperature: 30 °C

Sample Manager Temperature: $5 \pm 3 \, ^{\circ}\text{C}$

Injection Volume: 1 µL

Data Courtesy of: Neshita Kipuw, Pfenex Expression Technology


MS CONDITIONS:

Ionization Mode: ESI

Polarity: Positive

Full Scan: m/z 50-1000 Cone Voltage: 15 V

Gas Flow Pressure: 70-100 psi



AUTHORIZED DISTRIBUTOR

MZ-Analysentechnik GmbH, Barcelona-Allee 17 • D-55129 Mainz Tel +49 6131 880 96-0, Fax +49 6131 880 96-20 e-mail: info@mz-at.de, www.mz-at.de



