




INSTRUCTION MANUAL FOR CHIRALCEL[®] OD-H and CHIRALCEL[®] OJ-H

Please read this instruction sheet completely before using these columns

Column Description



CAUTION

The entire HPLC system including the injector and the injection loop must be flushed with a solvent compatible with the column and its storage solvent prior to connecting. Many of the solvents commonly used in HPLC eluents such as acetone, chloroform, DMF, dimethylsulfoxide, ethyl acetate, methylene chloride and THF may DESTROY the chiral stationary phase if they are present, even in residual quantities, in the system.

If an auto-sampler is used, then the solvent employed to flush this unit between injections should also be changed and the relevant solvent lines flushed.

Operating Conditions

	150 x 2.1 mm i.d. Analytical columns	150 x 4.6 mm i.d. 250 x 4.6 mm i.d. Analytical columns	250 x 10 mm i.d. Semi-prep. columns	250 x 20 mm i.d. Semi-prep. columns	
Flow rate direction	As indicated on the column label				
Typical Flow rate ${\mathbb O}$	~ 0.1 - 0.2 ml/min	~ 1 ml/min	~ 5 ml/min	~ 18 ml/min	
Pressure limitation	Should be maintained < 300 Bar (4350 psi) for maximum column life Adapt flow rates to column size.				
Temperature	0 to 40°C				

① The maximum flow rate depends on the mobile phase viscosity (mobile phase composition), and should be adjusted in accordance with the pressure upper's limit (i.e. 300 Bar).

Operating Procedure

• Please contact Chiral Technologies for further assistance before trying any solvents not mentioned below.

A - Mobile Phases

	Alkane ❶ ∕ 2-propanol ❷	Alkane❶/ Ethanol❷	Alkane❶/ MeOH❸	Alkane ❶ / Methyl- <i>tert</i> -butyl ether (MTBE)	MeOH 4 + S	CH₃CN ᢒ+ ❻ <u>No alkane at all</u>
CHIRALCEL [®] OD-H CHIRALCEL [®] OJ-H	100/0 to	100/0 to	100/0 to	100/0 to	0 to 100% EtOH or IPA in MeOH	0 to 100% IPA in CH ₃ CN
	0/100 0/100	85/15	50/50	0-15% ⑦ CH₃CN in MeOH	0 to 15% ⑦ MeOH or EtOH in CH₃CN	

• Alkane: n-hexane or iso-hexane or n-heptane. Some small selectivity differences may sometimes be found.

0

- **D** The retention is generally shorter with Ethanol than with 2-propanol.
- □ The retention is generally shorter with higher alcohol contents.
- □ The use of other alcohols such as 1-propanol, 1-BuOH, 2-BuOH etc...is possible, but effectiveness cannot be guaranteed.
- Due to limited miscibility of MeOH in Alkane, it is necessary to add an appropriate volume of EtOH together with MeOH in order to obtain homogenous solvent mixtures. A maximum of 5% MeOH in n-hexane only may be used without adding EtOH.
- Ideal starting conditions: MeOH/EtOH 50:50 (v/v) when alcohol mixtures are required
- The use of polar solvents as 100% methanol or 100% acetonitrile is possible with CHIRALCEL[®] OD-H & OJ-H columns. Nevertheless once the column is transferred to a polar mode <u>it should be dedicated to this specific application</u>.

To safely transfer the column from hexane to methanol or acetonitrile <u>or between different polar solvents</u>, **it is strongly recommended to use 100% 2-propanol as a transition mobile phase**.

- The column needs to be thoroughly washed with acetonitrile (~ 10 column volumes) prior to the first use in this solvent as mobile phase.
- 6
- □ Column particularly efficient in this range when such solvent mixtures are employed.
- □ Other alcohols such as 1-propanol, 1-BuOH, 2-BuOH etc...can also be used, but effectiveness cannot be guaranteed. Do not use mobile phases containing more than 15% of these alcohols

B – Additives

For basic samples or acidic samples, it is necessary to add an additive into the mobile phase in order to achieve the chiral separation:

- For primary amines mainly
- For primary amino alcohols mainly

Basic Samples	Acidic Samples		
Require	Require		
Basic modifiers	Acidic modifiers		
DEA Butyl amine® Ethanol amine®	TFA CH₃COOH		
< 0.5%	< 0.5%		
Typically 0.1%	Typically 0.1%		

Column Care / Maintenance

- **D** The use of a guard cartridge is highly recommended for maximum column life.
- □ Samples should be dissolved in the mobile phase and should be filtered through a membrane filter of approximately 0.5µm porosity.
- □ For alkane containing mobile phases, flush the column with Storage Solvent (Hexane / 2-propanol 9:1) when stored for more than one week.
- □ For columns dedicated to polar solvents, flush the column with the regular mobile phase without the additive.

^{CP} When washing is required, flush pure Ethanol for 3 hours (Columns used with alkane/alcohol mobile phase only).

 $igodol^*$ Before flushing with 100% Ethanol <u>use 100% 2-propanol as a transition mobile phase</u>.

 \Rightarrow STRONGLY BASIC solvent modifiers or sample solutions MUST BE AVOIDED, because they are likely to damage the silica gel used in this column.


Operating this column in accordance with the guidelines outlined here will result in a long column life.

⇒ If you have any questions about the use of these columns, or encounter a problem, contact:

In the USA: <u>questions@chiraltech.com</u> or call 800-6-CHIRAL

In the EU: <u>cte@chiral.fr</u> or call +33 (0)3 88 79 52 00

In India: chiral@chiral.daicel.com or call +91-40-2338-3700



AUTHORIZED DISTRIBUTOR

MZ-Analysentechnik GmbH, Barcelona-Allee 17 • D-55129 Mainz Tel +49 6131 880 96-0, Fax +49 6131 880 96-20 e-mail: info@mz-at.de, www.mz-at.de

Locations:

North/Latin America Chiral Technologies. Inc. 800 North Five Points Road West Chester, PA 19380 800 6 CHIRAL Tel: 610-594-2100 Fax: 610-594-2325 chiral@chiraltech.com

www.chiraltech.com

Europe

Chiral Technologies Europe Parc d'Innovation Bd Gonthier d'Andernach 67400 Illkirch Cedex, France Tel: +33-388-795-200 Fax: +33-388-667-166 cte@chiral.fr www.chiral.fr

India

Daicel Chiral Technologies (India) Pvt. Ltd. Lab No. 4A, Phase III IKP Knowledge Park Genome Valley, Turkapally, Shameerpet, Ranga Reddy Dist. Hyderabad-500 078, Telangana Tel: +91-40-2338-3700 Fax: +91-40-2348-0104 chiral@chiral.daicel.com

CHIRALCEL, CHIRALPAK and CROWNPAK are registered trademarks of DAICEL CORPORATION